



CARACTÉRISTIQUES TECHNIQUES :

Type	Puissance brute		Puissance utile		η utile à Pn mini	η utile à Pn maxi	η utile à 30 % Pn maxi	Contre pression mb	Pression de service (bars)	T° départ maxi (°C)	T° retour mini (°C)	Capacité eau (litres)
	Min	Max	Min	Max								
HEB 90	80	90	77	87	96.2	96	95.1	0.8	5	100	55	161
HEB 110	90	115	87	110	96.2	95.8	95.1	1.5	5	100	55	161
HEB 160	115	166	110	159	96	95.6	95.6	1.3	5	100	55	191
HEB 210	166	217	159	207	95.9	95.3	96.3	2.2	5	100	55	268
HEB 240	217	255	209	243	96.2	95.8	96.5	2.8	5	100	55	258
HEB 300	250	318	240	303	95.8	95.6	96.5	3.2	5	100	55	308
HEB 330	318	348	304	332	95.6	95.4	96.7	3.9	5	100	55	308
HEB 420	384	448	369	427	96.2	95.4	96.7	3.5	5	100	55	593
HEB 480	448	511	431	488	96.2	95.4	96.7	4.2	5	100	55	593
HEB 540	511	575	492	549	96.2	95.4	96.7	3.4	5	100	55	758
HEB 610	575	639	553	610	96.2	95.4	96.7	4.5	5	100	55	758
HEB 730	639	766	615	731	96.2	95.4	96.7	5.3	5	100	55	839
HEB 850	766	896	737	855	96.2	95.4	96.7	6	6	100	55	1080
HEB 1050	896	1100	962	1049	96.2	95.4	96.7	3.3	6	100	55	1350
HEB 1240	1020	1300	981	1240	96.2	95.4	96.7	5.3	6	100	55	1480
HEB 1530	1300	1600	1251	1526	96.2	95.4	96.7	4.7	6	100	55	1716
HEB 2000	1600	2100	1539	2003	96.2	95.4	96.7	5.1	6	100	55	2000
HEB 2300	2100	2400	2020	2290	96.2	95.4	96.7	7.6	6	100	55	2000

ÉQUIPEMENTS ET PRESTATIONS ASSOCIÉS :

