



CARACTÉRISTIQUES TECHNIQUES

Réf.		Débit air (m³)	Puissance thermique (kW)	Vit. ventilateur (tr/mn)	Niv. Sonore *dB(A)	T° soufflage (°C)	Portée d'air (m)	Puissance électrique (W)	Poids Vide (Kg)	Alim. élec. 50Hz V
WA 46.11	mini	1140	4.5	900	31	27	5.5	50	19	triphasé 400V - IP 44
	maxi	1670	5.9	1.400	40	26	8	150	19	
WA 46.12	mini	1040	7.8	900	32	39	5.5	50	22	
	maxi	1560	10.2	1400	41	36	8	150	22	
WA 46.13	mini	960	9	900	32	45	5.5	50	24	
	maxi	1450	11.9	1400	41	42	8	150	24	
WA 46.21	mini	1560	6.3	900	33	27	7.5	50	22	
	maxi	2370	8.3	1400	41	26	11	150	22	
WA 46.22	mini	1440	10.9	900	34	39	7.5	50	25	
	maxi	2200	14.3	1400	42	36	11	150	25	
WA 46.23	mini	1380	12.3	900	34	44	7.5	50	27	
	maxi	2100	16.2	1400	42	40	11	150	27	
WA 46.31	mini	2230	9.5	900	35	28	10	90	26	
	maxi	3400	12.7	1400	44	26	14	250	26	
WA 46.32	mini	2170	16.5	900	36	39	10	90	30	
	maxi	3300	21.9	1400	45	36	14	250	30	
WA 46.33	mini	2100	19	900	36	44	10	90	33	
	maxi	3200	25.4	1400	45	41	14	250	33	
WA 46.41	mini	2910	12.4	900	36	28	12	90	30	
	maxi	4250	16.4	1400	45	27	16	250	30	
WA 46.42	mini	2720	21.4	900	37	40	12	90	34	
	maxi	3980	28.3	1400	46	38	16	250	34	
WA 46.43	mini	2600	24.5	900	37	46	12	90	38	
	maxi	3800	32.4	1400	46	43	16	250	38	
WA 46.51	mini	3630	16.4	900	40	29	15	120	33	
	maxi	5600	21.6	1400	48	27	20	400	33	
WA 46.52	mini	3560	28.4	900	41	41	15	120	40	
	maxi	5500	37.3	1400	49	37	20	400	40	
WA 46.53	mini	3500	32.4	900	41	45	15	120	44	
	maxi	5400	42.6	1400	49	41	20	400	44	
WA 46.61	mini	4790	21.5	900	43	28	18	185	38	
	maxi	7400	27.6	1400	51	26	25	480	38	
WA 46.62	mini	4670	37.1	900	44	41	18	185	46	
	maxi	7200	47.6	1400	52	36	25	480	46	
WA 46.63	mini	4550	42.7	900	44	45	18	185	51	
	maxi	7000	54.8	1400	52	40	25	480	51	
WA 68.71	mini	4400	19.8	700	42	28	18	185	46	triphasé 400V - IP 44
	maxi	5800	23.6	900	52	27	24	370	46	
WA 68.72	mini	4100	34.2	700	43	42	18	185	55	
	maxi	5400	40.7	900	53	39	24	370	55	
WA 68.73	mini	3800	40.4	700	43	49	18	185	61	
	maxi	5200	49.2	900	53	45	24	370	61	
WA 68.81	mini	6000	27.8	700	44	39	20	250	55	
	maxi	8500	33.5	900	54	27	26	550	55	
WA 68.82	mini	5500	48	700	45	42	20	250	66	
	maxi	7600	57.8	900	55	39	26	550	66	
WA 68.83	mini	5000	54.8	700	45	49	20	250	73	
	maxi	7000	66.9	900	55	45	26	550	73	
WA 68.91	mini	8000	36	700	49	28	21	370	65	
	maxi	10600	43.4	900	57	27	28	750	65	
WA 68.92	mini	7500	62.2	700	50	41	21	370	79	
	maxi	10000	74.9	900	58	39	28	750	79	
WA 68.93	mini	7000	74.6	700	50	49	21	370	88	
	maxi	9500	90.9	900	58	45	28	750	88	
WA 68.101	mini	9500	42.2	700	51	28	22	550	79	
	maxi	12500	55.2	900	60	28	30	1100	79	
WA 68.102	mini	8800	72.9	700	52	41	22	550	95	
	maxi	11900	90	900	61	40	30	1100	95	
WA 68.103	mini	8.450	89.5	700	52	49	22	550	106	
	maxi	11400	109.2	900	61	44	30	1100	106	